

## Pulmonex™ II Xenon System *continued*

Dimensions:	48.5" H x 22" D x 20.5" W	Shipping Weight:	375 lb
Motor:	UL approved. 12 volt DC	Certifications:	ETL
Electrical Requirements:	115 VAC, 1 amp, 50/60 Hz	Warranty:	One year



132-503 Pulmonex II Xenon System  
Double-Trap, 115 VAC

Related:  
 136-755 Xenon Trap Monitor  
 150-315 Automatic Xenon Dispenser  
 132-319 Replacement Charcoal Trap  
 132-555 Refillable Cartridge, Soda-Lime or Drierite  
 130-900 Free Breathing Hose Kit

### Automatic Xenon Dispenser

- Attaches to the front of the Pulmonex System without tools
- Simply load the xenon vial into the supplied plunger assembly and at the precise moment you want the delivery of xenon, simply press the dispense button
- Xenon is automatically delivered to the patient



150-315 Automatic Xenon Dispenser  
*Includes 72" Flexible Tubing with Luer-Lock Adaptor*  
 150-317 Tubing, 72" Luer-lock adapter, 5/Pkg

### Xenon Trap Monitor

- Continuously monitors trap effluent during a xenon study, meeting compliance requirements in most states
- An exhaust hose connects from the Pulmonex II exhaust port to the Xenon Trap Monitor's intake port, making it the perfect complement to the Pulmonex II Xenon System to ensure a safe environment
- Simple to operate; all controls are located on the front panel
- Counting results are displayed with both audible and visual signals to indicate when the xenon trap exhaust port exceeds the threshold of 99 pCi/mL
- The unit can also check background levels and perform a self-test for proper operation using a check source (a 10 µCi Cs-137 Check source is required to calibrate the monitor- not included)
- Includes all the hardware necessary to mount the unit directly to the Pulmonex II Xenon System

Dimensions: 6" W x 7" L x 4" H  
 Lead Shielding: 1/2" thick  
 Input: 22 mm Hose Adaptor  
 Detector: Halogen Quenched GM Tube, 1.1 cm diameter, 2 mg/cm<sup>2</sup> mica window  
 Voltage: 500 volts regulated  
 Buttons: On/ Off, Next/ Mute  
 Display: 4 Digit LED, 4 RGB Function LEDs (Self Test, Background, Check Source or Count)  
 Readings: pCi/ml or counts  
 Speaker: Internal, beeps in alarm mode  
 Background Count Time: 1 minute  
 Power: 18 volts, UL approved, external; 115 VAC power adapter  
 Weight: 5.25 lb  
 Warranty: One year



136-755 Xenon Trap Monitor  
*Mounts to Pulmonex II Xenon Systems*  
 101-103 Check Source, Cs-137, 10 µCi  
*Uncalibrated, 1" Dia x .25" thick*

Mounts directly to the 132-503 for continuous monitoring